



Latitude Pro Arc Flash 7' Web SRL-P

*See chart for part numbers, hook configurations, and product weights

FEATURES :

- Complete confidence in full, continuous retraction with side payout housing.
- Reliable internal braking system eliminates need for external shock pack.
- 360/180° attachment point offers full range of motion.
- High strength semi-sealed assembly protects internal components from debris to extend product life.
- Translucent housing allows easy inspection of webbing, reserve line and pawl assembly.
- Trusted Kevlar® webbing and Nomex® flame-resistant label cover.
- Minimal exposed webbing protects against UV damage.
- Single leg and dual leg options available.
- Available with various hook and attachment options, see chart.
- All components are Z359.12 compliant.



Class

1

Anchor at or above dorsal D-ring

Product shown:
020-5221

USER WEIGHT CAPACITY

ANSI	130-310 lbs. (59-140.6 kg)
OSHA	Up to 420 lbs. (190.5 kg)

STANDARD COMPLIANT WITH

ANSI	Z359.14-2021
OSHA	1910.140, 1910.66
ASTM	F887

ANSI CLASS 1 (ABOVE D-RING)

Max. arrest force	≤ 1,800 lbs. (816.5 kg)
Avg. arrest force	≤ 1,350 lbs. (612.4 kg)
Max. arrest distance	≤ 42 in. (107 cm)
Actual arrest distance	≤ 27 in. (69 cm)
Max. free fall distance	24 in. (61 cm)
Use below d-ring	not permitted
Min. required fall clearance	5 ft. 9 in. (1.8 m)
For full clearance requirements, see user instructions	

OSHA (BELOW D-RING)

Max. arrest force	≤ 1,800 lbs. (816.5 kg)
Avg. arrest force	≤ 900 lbs. (408.2 kg)
Max. arrest distance	N/A
Actual arrest distance	≤ 24 in. (61 cm)
Max. free fall distance	24 in. (61 cm)
Use below d-ring	2 ft. (0.6 m)
Min. required fall clearance	7 ft. 6 in. (2.3 m)
For full clearance requirements, see user instructions	

MATERIAL SPECIFICATION

Webbing	20 mm Kevlar® webbing
Housing	Clear resin
Bracket	Steel, aluminum (dependent on configuration)
Hook options	Steel, aluminum, dielectric (dependent on configuration)

« Producto Distribuido por Fagy Peru® »

www.fagy.com.pe - www.ventadeepps.com



SAFEWAZE

TECHNICAL DATA SHEET

Latitude Pro Arc Flash 7' Web SRL-P

LATITUDE

PRO ARC FLASH

Standards: ANSI Z359.14-2021

OSHA 1910.140, 1910.66

ASTM F887

Capacity: ANSI 130-310 lbs. (59-141 kg)

OSHA Up to 420 lbs. (191kg)

CONNECTOR										ATTACHMENT														
Part Number	Single Leg (S) / Dual Leg (D)	Working Length (ft.)	Lifeline Material	Lifeline Dimensions (in.)	Housing Material	Weight (lbs.)	LI Steel Swivel Snap Hook ①	LI Steel Swivel Snap Hook ②	Dielectric Snap Hook ③	Steel Tie Back Hook ④	LI Steel Swivel Rebar Hook ⑤	Steel Swivel Rebar Hook ⑥	Steel Swivel Rebar Hook ⑦	Steel Swivel Rebar Hook ⑧	ALU Swivel Rebar Hook ⑨	ALU Swivel Rebar Hook ⑩	ALU Swivel Rebar Hook ⑪	ALU Swivel Rebar Hook ⑫	ALU Swivel Rebar Hook ⑬	ALU Swivel Rebar Hook ⑭	ALU Swivel Rebar Hook ⑮	ALU Swivel Rebar Hook ⑯	ALU Swivel Rebar Hook ⑰	
020-5200	1	S	7	Kevlar® Webbing	.7X.05	Clear Resin	3.0	X											X					
020-5201	1	S	7	Kevlar® Webbing	.7X.05	Clear Resin	2.8					X							X					
020-5202	1	S	7	Kevlar® Webbing	.7X.05	Clear Resin	3.0		X										X					
020-5203	1	S	7	Kevlar® Webbing	.7X.05	Clear Resin	3.6								X				X					
020-5204	1	S	7	Kevlar® Webbing	.7X.05	Clear Resin	2.7	X																X
020-5205	1	S	7	Kevlar® Webbing	.7X.05	Clear Resin	3.7					X												X
020-5206	1	S	7	Kevlar® Webbing	.7X.05	Clear Resin	2.5		X															X
020-5207	1	S	7	Kevlar® Webbing	.7X.05	Clear Resin	3.3								X									X
020-5208	1	S	7	Kevlar® Webbing	.7X.05	Clear Resin	2.8			X														X
021-5285	1	S	7	Kevlar® Webbing	.7X.05	Clear Resin	3.1			X									X					
020-5213	1	D	7	Kevlar® Webbing	.7X.05	Clear Resin	5.1	X																X
020-5214	1	D	7	Kevlar® Webbing	.7X.05	Clear Resin	7.1					X												X
020-5215	1	D	7	Kevlar® Webbing	.7X.05	Clear Resin	4.7		X															X
020-5216	1	D	7	Kevlar® Webbing	.7X.05	Clear Resin	6.3								X									X
020-5221	1	D	7	Kevlar® Webbing	.7X.05	Clear Resin	5.5			X														X
020-5217	1	D	7	Kevlar® Webbing	.7X.05	Clear Resin	5.0	X																X
020-5218	1	D	7	Kevlar® Webbing	.7X.05	Clear Resin	7.1					X												X
020-5219	1	D	7	Kevlar® Webbing	.7X.05	Clear Resin	4.7		X															X
020-5220	1	D	7	Kevlar® Webbing	.7X.05	Clear Resin	6.3								X									X
022-5308	1	S	7	Kevlar® Webbing	.7X.05	Clear Resin	2.5			X												X		
022-5309	1	S	7	Kevlar® Webbing	.7X.05	Clear Resin	2.5									X					X			
022-5310	1	S	7	Kevlar® Webbing	.7X.05	Clear Resin	2.5									X					X			



« Producto Distribuido por Fagy Peru® »

www.fagy.com.pe - www.ventadeepps.com